

ABSOLUTE OPTICAL ROTARY ENCODER MULTITURN BIT PARALLEL



Main Features

- Compact and Heavy-Duty Industrial Model
- Interface: Bit Parallel, Push Pull, Short Circuit Proof
- Input: Preset (optional) and Latch
- Housing: \varnothing 58 mm
- Shaft: \varnothing 6 or 10 mm , Hollow- \varnothing 15 mm
- Max. 65,536 Steps per Revolution (16 Bit)
- Max. 16,384 Revolution (14 Bit)
- Code: Gray / Binary
- EMC: EN61000-6-2, EN61000-6-4, CE

Mechanical Structure

- Aluminum Flange and Housing
- Stainless Steel Shaft
- Precision Ball Bearings with Sealing or Cover Rings
- Code Disc made of unbreakable and Durable Plastic

Applications

Sensing of

- Angles
- Distances
- Tracks
- Inclinations
- Differences between two or more Axes

Electrical Features

- Temperature insensitive IR-Opto-Receiver-ASIC with integrated Signal Conditioning
- Only one IR-Transmitter-Diode per Opto-ASIC
- Highly Integrated Circuit in SMD-Technology
- Polarity Inversion Protection
- Over-Voltage-Peak Protection

ABSOLUTE OPTICAL ROTARY ENCODER MULTITURN BIT PARALLEL

1 Technical Data

1.1 Electrical Data

Outputs	Bit-parallel, push pull
Output level "high"	~ supply voltage (load dependent)
Output current	Max. 20 mA each channel
Cycle time	< 10 μ s (< 150 μ s with preset version)
Step frequency	Version with Preset: 4,5 kHz Version without Preset: 50 kHz
Turn on time	< 1 s
Accuracy of division	$\pm \frac{1}{2}$ LSB (12 Bit), ± 2 LSB (16 Bit)
EMC	Emitted interference: EN 61000-6-4, Noise immunity: EN 61000-6-2
Supply voltage	10-30 V DC (absolute limits) ¹
Current consumption	Max. 400 mA (10 V DC), max. 180 mA (24 V DC)
Electrical lifetime	> 10 ⁵ h
Connection	Connector or cable exit 1 meter

1) Supply voltage according to EN 50 178 (safety extra-low voltage)

1.2 Mechanical Data

Housing	Aluminum, optional stainless steel
Lifetime	See next table
Shaft loading	Axial 40 N, radial 110 N
Inertia of rotor	$\approx 30 \text{ gcm}^2$
Friction torque	$\leq 3 \text{ Ncm}$ (version without shaft sealing)
RPM (continuously)	Max. 6,000
Shock (EN 60068-2-27)	$\leq 100 \text{ g}$ (halfsine, 6 ms)
Permanent shock (EN 60068-2-29)	$\leq 10 \text{ g}$ (halfsine, 16 ms)
Vibration (EN 60068-2-6)	$\leq 10 \text{ g}$ (10 Hz ... 2,000 Hz)
Weight, multi-turn (stainless steel)	$\approx 400 \text{ g}$ ($\approx 800 \text{ g}$)

ABSOLUTE OPTICAL ROTARY ENCODER MULTITURN BIT PARALLEL

1.3 Flasch

Flange	Synchro	Clamp	Hollow shaft
Shaft diameter	Ø 6 mm / 10 mm	Ø 10 mm	Ø 15 mm
Shaft length or hollow shaft depth	10 mm / 20mm	20 mm	15 – 30 mm

1.4 Minimal Live Cycle Mechanical

Flange group	Live cycle in 10^8 turns on F_a / F_r		
	40 N / 60 N	40 N / 60 N	40 N / 60 N
C10 (Clamp flange Ø 10 x 20)	247	247	247
S10 (Synchro flange Ø 10 x 20)	262	262	262
S6 (Synchro flange Ø 6 x 10) without shaft sealing	822	822	822

S6 (Synchro flange ø6 x 10) with shaft sealing: maximal 20 N axial, 80 N radial

1.5 Environmental Conditions

Operating temperature	-40 – +85°C ¹
Storage temperature	-40 – +85°C ¹
Humidity	98 % (without liquid state)
Protection Class (EN 60529)	Casing side: IP 65
	Shaft side: IP 64 (optional with shaft sealing: IP66)

¹) Cable eXIT: -30 – +70 °C (stationary cable), -5 – +70°C (moving cable)


ABSOLUTE OPTICAL ROTARY ENCODER MULTITURN BIT PARALLEL

2 Interface

Push Pull

Transmission	Data transmission via two transistors in push-pull circuit
Transfer	Transfer distance up to 50 m
Shielded lines	Shielded lines are essential to attain extremely high noise immunity
Connectable	Connectable to all usual PLC concepts with digital I/Os
Optional	Binary code transmission with integrated latch function

Output Circuit




ABSOLUTE OPTICAL ROTARY ENCODER MULTITURN BIT PARALLEL

2.1 Electrical Interface

Signals	26 Pin Connector	Cable Color	Signals	26 Pin Connector	Cable Color
Bit 1	Pin 1	White	Bit 20	20	Pink-Brown
Bit 2	2	Brown	Bit 21	21	White-Blue
Bit 3	3	Green	Bit 22	–	Brown-Blue
Bit 4	4	Yellow	Bit 23	–	White-Red
Bit 5	5	Grey	Bit 24	–	Brown-Red
Bit 6	6	Pink	Bit 25	–	White-Black
Bit 7	7	Blue	Preset (opt.)	22	Brown-Black
Bit 8	8	Red	Latch	23	Grey-Green
Bit 9	9	Black	Complement	24	Yellow-Grey
Bit 10	10	Violet	+U _b = 10-30 V	25	Pink-Green
Bit 11	11	Grey-Pink	GND	26	Yellow-Pink
Bit 12	12	Blue-Red			
Bit 13	13	White-Green			
Bit 14	14	Brown-Green			
Bit 15	15	White-Yellow			
Bit 16	16	Yellow-Brown			
Bit 17	17	White-Grey			
Bit 18	18	Grey-Brown			
Bit 19	19	White-Pink			

26 Pin Connector (Male)



COMPLEMENT- Input		Encoder counting direction at clockwise rotation (as seen on shaft)
Function	Level	
Direction of rotation Switch time < 3 μs	0 (Input = N.C. ¹ or GND)	Up
	1 (Input to + U _b or ≥ 4,5 V)	Down
Preset-Input (optional, should not used during shaft rotation)		
Function	Level	
Preset	0 (Input = N.C. ¹ or GND)	Use the current value
	1 (Input to + U _b or ≥ 4.5 V)	Set preset value to 0 (after 100ms)
Latch-Input		
Function	Level	
Latch Latch time < 3 μs	0 (Input = N.C. ¹ or GND)	Use the current value
	1 (Input to + U _b or ≥ 4.5 V)	Latch the value


1) No ledge on connector disposed

ABSOLUTE OPTICAL ROTARY ENCODER MULTITURN BIT PARALLEL

3 Mechanics Drawing


3.1 Synchroflansch (S) (Two Versions available)

Synchro Flange	d / mm	l / mm
Version S06	6 _{f6}	10
Version S10	10 _{h8}	20



Cable exit		62
Connector	axial	62
	radial	78


Connector Exit (only for max. 21 Bit)



ABSOLUTE OPTICAL ROTARY ENCODER MULTITURN BIT PARALLEL


3.2 Clamp Flange (C)

Cable Exit (~ Ø 10 mm)



Cable exit		62
Connector	axial	62
	radial	78

Connector Exit (only for max. 21 Bit)



ABSOLUTE OPTICAL ROTARY ENCODER
MULTITURN BIT PARALLEL

3.4 Mounting Instructions

Do not tighten the clamp ring unless the machine shaft is properly inserted into the bore of the hollow shaft.

The diameter of the hollow shaft can be reduced to 12 mm, 10 mm or 8 mm by using an adapter (this

reducing adapter can be pushed into the hollow shaft). Allowed shaft movements of the drive element are listed in the table.

	Axial	Radial
Static	$\pm 0.3 \text{ mm}$	$\pm 0.5 \text{ mm}$
Dynamic	$\pm 0.1 \text{ mm}$	$\pm 0.2 \text{ mm}$

ABSOLUTE OPTICAL ROTARY ENCODER MULTITURN BIT PARALLEL

4 Models / Ordering Description

Description	Type Key								
IXARC Optical	OCD-	--	00	-	--	--	-	--	-
Interface Push Pull		PP							
With Preset		P1							
Version			00						
Code	Gray			G					
	Binary			B					
Bits for revolutions ¹	16			04					
	256			08					
	4.096			12					
	16.384			14					
Steps per revolution ¹	4.096 (0,09°)			12					
	8.192 (0,04°)			13					
	65.536 (0,005°)			16					
Flange	Clamp Flange						C		
	Synchro Flange						S		
	Blind Hollow Shaft						B		
Shaft	10 mm						10		
	06 mm						06		
	15 mm (only for hollow shaft)						15		
Mechanical Options	Without							0	
	Shaft sealing							S	
	Stainless steel (only axial exit possible)							V	
	Customized							C	
Connection	Shaft sealing								PAT
	Stainless steel (only axial exit possible)								PRT
	Customized								CAW
	1m cable exit, radial, max. 25 bit ²								CRW

Standard = **bold**, further models on request

1) Total Resolution on connector exit max. 21 bit, on cable exit max. 25 bit

2) Not in stainless version

ABSOLUTE OPTICAL ROTARY ENCODER MULTITURN BIT PARALLEL

5 Accessories

Description		Type
Connector, counterpart	Circular connector, 26 pins	PAT
Cable for PAT	28 x 0,14 mm ² + 2 x 1,5 mm ²	STK-30
Shaft coupling ¹	Drilling: 10 mm	GS 10
	Drilling: 6 mm	GS 06
Clamp disc ¹	4 pcs. / AWC	SP 15
Clamp ring ¹	2 pcs. / AWC	SP H
Reducing adapter ²	15 mm to 14 mm	RR14
Reducing adapter ²	15 mm to 12 mm	RR12
Reducing adapter ²	15 mm to 10 mm	RR10
Reducing adapter ²	15 mm to 8 mm	RR8

1) Not for hollow shaft

2) Only for hollow shaft

ABSOLUTE OPTICAL ROTARY ENCODER MULTITURN BIT PARALLEL

6 Check Out Some of the Other POSITAL Products



Absolute Magnetic Encoders for Industrial Environment

To measure rotary movements or rotary displacements, an absolute magnetic rotary encoder can be used. The contact-free measuring sensor stage of the IXARC Magnetic Sensor does not have any abrasion. The Sensor can be connected directly to digital control

units via SSI, CANopen or Analog Interface.

[More Information](#)



Heavy Duty Stainless steel Magnetic Encoders for the Toughest Environments

Its stainless steel housing and high protection class of IP69K makes the IXARC Magnetic Heavy Duty rotary encoder resistant against active chemical cleaning and corrosion. Combined with the sturdy ball bearings this sensor is an ideal choice for reliable measurement under extreme environmental conditions and outdoor applications.

[More Information](#)



Tilt Sensors to Measure Inclinations up to 360°

TILTIX is developed on advanced MEMS technology based capacitance measurement. The sensor is a pre-calibrated device which can be put into immediate operation, upon simple and easy installation with a three point mount and setting of preset. Its compact design, installation “anywhere” and other versatile features makes it an ideal choice for very accurate measurement.

[More Information](#)

7 Disclaimer

© FRABA N.V. all rights reserved. We do not assume responsibility for technical inaccuracies or omissions. Specifications are subject to change without notice.